

| Model | K11G | K13,5G | K15G |
|--|---------------------|---------------------|---------------------|
| Output kW | 11 | 13,5 | 15 |
| Sauna room min. m ³ | 9 | 11 | 14 |
| Sauna room max. m ³ | 16 | 20 | 24 |
| Sauna room height min. cm | 190 | 210 | 210 |
| Stone capacity max. kg | 60 | 60 | 60 |
| Dimensions width mm | 505 | 505 | 505 |
| Dimensions height mm | 700 | 700 | 700 |
| Dimensions depth mm | 430 | 430 | 430 |
| Weight kg | 25 | 25 | 25 |
| Supply voltage 3-phase | 400 V 3N | 400 V 3N | 400 V 3N |
| Connecting cable mm ² | 5x2,5 | 5x4,0 | 5x6,0 |
| Fuse A | 3x16 | 3x20 | 3x25 |
| Control unit | C150, C150VKK, C260 | C150, C150VKK, C260 | C150, C150VKK, C260 |
| Safety distance A to wall mm | 70 | 100 | 100 |
| Safety distance B to front lower platform mm | 50 | 50 | 50 |
| Safety distance C to upper platform mm | 70 | 100 | 100 |
| Safety distance D to ceiling mm | 1200 | 1400 | 1400 |

